222+2

Serbian Academy of Sciences and Arts, Belgrade,
Technical Faculty, Čačak,
Center for Solid State Physics & New Materials, Institute of Physics,
Belgrade,

Institute of Technical Sciences of SASA, Belgrade

## **Physics and Technology of Materials**



## ANALYSIS OF ISOTHERMAL SINTERING OF ZINC-TITANATE DOPED WITH MgO

N. Obradovic<sup>1</sup>, S. Stevanovic<sup>1</sup>, M. Mitric<sup>2</sup>, M. V. Nikolic<sup>3</sup>, M. M. Ristic<sup>4</sup>

<sup>1</sup> Institute of Technical Sciences of SASA, Knez-Mihailova 35/IV, 11000 Belgrade, Serbia,

<sup>2</sup>The Vinca Institute of Nuclear Sciences, Belgrade, Serbia,

<sup>3</sup>Center for Multidisciplinary Studies, University of Belgrade, K. Viseslava 1a, 11000 Belgrade, Serbia,

<sup>4</sup>Serbian Academy of Sciences and Arts, Knez-Mihailova 35/IV, 11000 Belgrade, Serbia

The aim of this work was analysis of isothermal sintering of zinc titanate ceramics doped with MgO obtained by mechanical activation. Mixtures of ZnO,  $TiO_2$  and MgO (0, 1.25 and 2.5%) were mechanically activated 15 minutes in a planetary ball mill. The powders obtained were pressed under different pressures and the results were fitted with a phenomenological compacting equation. Isothermal sintering was performed in air for 120 minutes at four different temperatures. Structural characterization of  $ZnO-TiO_2-MgO$  system after milling and sintering was performed at room temperature using XRPD measurements. DTA measurements showed different activation energies for pure and doped  $ZnO-TiO_2$  systems. The main conclusions are that doped zinc titanate samples achieve higher densities after sintering and that addition of MgO stabilizes the crystal structure of zinc titanate.